

Enhance™ HD

Ultra high strength floor polish



Premium, acrylic floor polish for high wear, high traffic areas. Dries to an extra durable, brilliant, very high gloss, wet look, slip resistant finish.

28% total solids with excellent levelling properties.

Twice the durability of ordinary polishes.

- Ideal for very high traffic areas.
- Can be burnished using UHS 2200+ ROM machines.
- Reduces stripping cycles.
- Excellent levelling properties for easy application and to ensure a smooth even finish.
- Suitable for hard floors: vinyl, rubber, terrazzo, marble, concrete & sealed surfaces.
- Coverage per 5 L - 300/400 sq. metres for 1 coat.

RECOMMENDED FLOOR SURFACES:

Vinyl composition tile (VCT), terrazzo, marble, concrete, quarry tile.

This UHS floor finish is formulated with a special blend of resins, waxes & polymers to provide a long lasting, high gloss finish that can stand up to the heavy daily traffic and maintenance that is seen in retail or institutional facilities.

INITIAL APPLICATION:

For a floor that has been stripped, properly neutralised, rinsed and allowed to dry thoroughly, apply 5-6 thin coats of **ENHANCE HD** using a clean synthetic mop. Allow the floor to dry thoroughly between coats and prior to burnishing. Drying time depends on a number of factors. At 20°C approx. 30 minutes between coats and 3 hours minimum before burnishing.

Optional: Apply 2 thin coats of **SEALANT B** floor sealer for old or porous floors or for high traffic areas before applying **ENHANCE HD**.

ROUTINE MAINTENANCE:

- Sweep floor daily with a dust mop.
- To clean floor use a mop or automatic scrubber with a neutral cleaner.
- Restore shine as needed with **CLEAN & SHINE** maintenance cleaner to improve gloss and repair polish damage or wear.
- Burnish with ultra high speed machine and pad. One pass is all that is usually required.
- When desired results can no longer be achieved by routine maintenance, strip floor using **SURE STRIP** and re-apply **ENHANCE HD** as shown in initial application.

5l

Order Code: A135EEV2

Pack: 2 x 5 litre (10.77 kg)

Pallet: 60 Packs

PRODUCT INFORMATION:

Appearance:	Opaque white liquid
Odour:	Characteristic
pH - undiluted:	8.0
Shelf life:	3 years

COMPOSITION:

Contains an aqueous dispersion of metallised acrylic co-polymers, wax emulsion, plasticisers, coalescent, defoamer, levelling agent & preservative.

BIODEGRADABILITY: All surfactants used in Evans Vanodine products comply with the current European Regulations concerning biodegradability & protection of the environment.

QUALITY ASSURANCE:

EVANS VANODINE INTERNATIONAL PLC operates under an ISO 9001 Quality Management System Cert. No. FM 09535 and an ISO 14001 Environmental Management System Cert. No. EMS 506072 registered by the British Standards Institution.

REVISION DATE:

09/12/16



Evans Vanodine International plc

Brierley Road, Walton Summit, Preston, PR5 8AH, UK

www.evansvanodine.co.uk | Tel: +44 (0)1772 322200 | Fax: +44 (0)1772 626000



ISO
9001
Quality
Management

ISO
14001
Environmental
Management

