

# PRO-TWIN FOAMING SYSTEM

## Troubleshooting guide



SYMPTOM	PROBABLE CAUSE	REMEDY
No flow.	<ol style="list-style-type: none"><li>1 No water supply.</li><li>2 Clogged hydrolic parts.</li></ol>	<ol style="list-style-type: none"><li>1 Open the water supply outside tap, select 'product' or 'rinse', turn on the spray gun.</li><li>2 Check the water supply filter (input station). Check the venturi.</li></ol>
Product is not mixed or dosed correctly	<ol style="list-style-type: none"><li>1 The foot filter is clogged.</li><li>2 The calibration nozzle is clogged.</li><li>3 Insufficient water pressure.</li><li>4 The chemical product container is empty.</li><li>5 The suction hose is not properly connected to the elbow fitting.</li><li>6 The suction hose is crimped somewhere.</li><li>7 Debris or solids in the venturi.</li></ol>	<ol style="list-style-type: none"><li>1 Clean or replace the filter.</li><li>2 Clean or replace the nozzle.</li><li>3 A minimum pressure of 22PSI is required for correct operation; if the pressure is not correct, contact a plumber.</li><li>4 Refill or change the chemical product container.</li><li>5 Check that the suction hose is properly connected to the fitting, use a clamp for better grip.</li><li>6 Check that the suction hose is properly positioned.</li><li>7 Clean with water or compressed air (Warning: do not use tools to remove the lime deposits because you can affect the functioning of the venturi; only use anti-lime products).</li></ol>
Concentration too high	<ol style="list-style-type: none"><li>1 The nozzle is not fully inserted or wrong metering tip.</li></ol>	<ol style="list-style-type: none"><li>1 Check that the nozzle is securely plugged into the non-return valve or select a smaller metering tip.</li></ol>
The chemical product container fills with water	<ol style="list-style-type: none"><li>1 The non-return valve is clogged or worn.</li></ol>	<ol style="list-style-type: none"><li>1 Clean or replace the non-return valve.</li></ol>